

Vierkantstahlrohre

EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
 EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m



Abmessung mm		Gewicht kg/m	Basis Fr./m
9 x 9 x 1	gezogen	0.249	4.60
10 x 10 x 1	S2	0.281	1.70
	1.5 S2	0.397	2.10
12 x 12 x 1	S2	0.344	2.30
	1.5 S2	0.491	2.60
14 x 14 x 1.5	S2	0.585	3.30
15 x 15 x 1	S2	0.438	2.70
	1.5 S2	0.632	2.90
	2 S2	0.810	3.30
16 x 16 x 1.5	S2	0.679	3.60
	2 S2	0.872	4.60
18 x 18 x 1	S2	0.532	3.20
	1.5 S2	0.773	4.00
	2 S2	0.998	5.60
20 x 20 x 1	S2	0.595	2.70
	1.5 S2	0.868	3.40
	2 S2	1.124	3.90
	2.5 S1	1.363	7.20
	2.5 S2	1.363	8.10
	3 S1	1.450	8.30
3 S2	S2	1.450	9.20
22 x 22 x 1.5	S2	0.962	5.30
	2 S2	1.249	6.90
	2.5 S2	1.520	9.30
25 x 25 x 1	S2	0.752	4.10
	1.5 S2	1.103	4.40
	2 S2	1.438	5.00
	2.5 S1	1.756	6.50
	2.5 S2	1.756	7.10
	3 S1	1.921	9.10
3 S2	1.921	10.10	
28 x 28 x 2	S2	1.626	8.90
	2.5 S2	1.991	13.20
30 x 30 x 1.5	S2	1.339	5.20
	1.5 S4 (SVZ)	1.339	6.80
	2 S2	1.752	6.10
	2 S3	1.752	9.30
	2 S2, geschabt	1.752	8.00
	2.5 S1	2.148	7.20
2.5 S2	S2	2.148	8.20
	S3	2.148	12.50
3 S1	S1	2.392	7.30
	S2	2.392	9.60
32 x 32 x 2	S2	1.877	11.30
	2.5 S2	2.305	14.30
34 x 34 x 2	S2	2.003	11.60

Abmessung mm		Gewicht kg/m	Basis Fr./m
35 x 35 x 1.5	S2	1.574	6.30
	2 S2	2.066	7.10
	2 S2, geschabt	2.066	9.30
	2.5 S1	2.541	9.20
	2.5 S2	2.541	10.00
	3 S1	2.863	9.70
3 S2	S2	2.863	13.50
38 x 38 x 2	S2	2.254	13.70
	3 S2	3.145	20.20
40 x 40 x 1.5	S2	1.810	7.20
	2 S2	2.380	7.80
	2 S2, geschabt	2.380	10.20
	2.5 S1	2.933	9.90
	2.5 S2	2.933	10.60
	3 S1	3.334	10.10
3 S2	S2	3.334	13.20
	4 S1	4.252	12.90
4 S2	4.252	23.00	
45 x 45 x 2	S2	2.694	9.90
	2.5 S1	3.326	11.90
	2.5 S2	3.326	13.20
	3 S1	3.805	16.10
3 S2	3.805	20.60	
50 x 50 x 1.5	S2	2.281	15.00
	1.5 S4	2.281	19.50
	2 S2	3.008	10.00
	2 S2, geschabt	3.008	13.00
	2.5 S1	3.718	12.30
	2.5 S2	3.718	14.10
3 S1	S1	4.276	12.90
	S2	4.276	15.90
	4 S1	5.508	16.10
	4 S2	5.508	30.80
	5 S1	6.560	19.80
55 x 55 x 1.5	S2	2.516	14.80
	2 S2	3.322	15.80
	3 S2	4.747	29.90
	5 S1	7.345	39.00
60 x 60 x 2	S2	3.636	13.60
	2 S2, geschabt	3.636	17.70
	2.5 S1	4.503	14.90
	2.5 S2	4.503	16.50
	3 S1	5.218	15.20
	3 S2	5.218	20.20
4 S1	S1	6.764	20.40
	S2	6.764	34.10

Vierkantstahlrohre



EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
 EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m

Abmessung mm				Gewicht kg/m	Basis Fr./m	
60	x	60	x 5	S1	8.130	23.90
70	x	70	x 2	S2	4.264	16.40
				S1	6.160	19.90
				S2	6.160	39.90
				S1	8.020	24.00
				S2	8.020	55.00
80	x	80	x 2	S2	4.892	18.90
				S1	7.102	22.40
				S2	7.102	34.90
				S1	9.276	26.10
				S2	9.276	56.00
90	x	90	x 3	S1	8.044	26.00
				S1	10.532	34.00
				S1	14.410	43.90
100	x	100	x 3	S1	8.986	26.80
				S1	11.788	33.50
				S2	11.788	86.00
				S1	14.410	43.90
120	x	120	x 3	S1	10.870	35.10
				S1	14.300	43.80
				S1 ^{S355}	26.408	79.70
140	x	140	x 3	S1	12.754	38.90

Abmessung mm	Gewicht kg/m	Basis Fr./m
-----------------	-----------------	----------------

weitere Abmessungen auf Anfrage

- S1 (M) = rohschwarz aus E235
- S2 (BKM) = gebeizt aus E195, E235 oder DD12
- S3 (WBKV) = aus Kaltband, mit schöner Oberfläche, gut biegsam
- S4 (SVZ) = sendzimirverzinkt
- geschabt = ohne Innengrat, ausgeschabte oder flacherollte Innennaht

Rechteckstahlrohre

EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
 EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m



Abmessung mm		Gewicht kg/m	Basis Fr./m
15 x 10 x 1.5	S2	0.514	2.60
20 x 10 x 1.5	S2	0.632	2.90
20 x 10 x 2	S2	0.810	3.90
20 x 15 x 1.5	S2	0.750	3.50
20 x 15 x 2	S2	0.967	4.30
25 x 10 x 1.5	S2	0.750	3.80
25 x 12 x 1.5	S2	0.797	7.40
25 x 12 x 2	S2	1.029	6.30
25 x 15 x 1.5	S2	0.868	4.10
25 x 15 x 2	S2	1.124	5.60
25 x 20 x 1.5	S2	0.985	5.60
25 x 20 x 2	S2	1.281	5.90
30 x 10 x 1.5	S2	0.868	3.80
30 x 10 x 2	S2	1.124	5.90
30 x 15 x 1.5	S2	0.985	3.90
30 x 15 x 2	S2	1.281	4.60
30 x 20 x 1.5	S2	1.103	4.40
30 x 20 x 2	S2	1.438	4.90
30 x 20 x 2.5	S2	1.756	7.00
30 x 25 x 1.5	S2	1.221	7.30
30 x 25 x 2	S2	1.595	7.90
35 x 10 x 2	S2	1.281	7.20
35 x 15 x 1.5	S2	1.103	4.40
35 x 15 x 2	S2	1.438	7.00
35 x 15 x 2	S4 (svz)	1.438	8.70
35 x 20 x 1.5	S2	1.221	6.20
35 x 20 x 2	S2	1.595	6.90
35 x 20 x 2.5	S2	1.952	10.90
35 x 25 x 2	S2	1.752	6.10
40 x 10 x 1.5	S2	1.103	5.40
40 x 10 x 2	S2	1.438	6.10
40 x 15 x 1.5	S2	1.221	5.30
40 x 15 x 2	S2	1.595	6.20
40 x 15 x 2.5	S2	1.952	10.90
40 x 20 x 1	S2	0.909	6.10
40 x 20 x 1.5	S2	1.339	5.40
40 x 20 x 2	S2	1.752	5.80
40 x 20 x 2	S3	1.752	8.90
40 x 20 x 2.5	S1	2.148	7.70
40 x 20 x 3	S1	2.392	10.10
40 x 20 x 3	S2	2.392	11.90
40 x 25 x 2	S2	1.909	7.40
40 x 25 x 2.5	S2	2.344	11.40
40 x 25 x 3	S1	2.627	11.10
40 x 25 x 3	S2	2.627	13.70

Abmessung mm		Gewicht kg/m	Basis Fr./m
40 x 30 x 1.5	S2	1.574	6.10
40 x 30 x 2	S2	2.066	7.10
40 x 30 x 2.5	S2	2.541	12.10
40 x 30 x 3	S1	2.863	11.60
40 x 30 x 3	S2	2.863	12.80
40 x 34 x 2	S2	2.191	14.50
45 x 15 x 1.5	S2	1.339	16.20
45 x 20 x 2	S2	1.909	9.80
45 x 25 x 1.5	S2	1.574	17.50
45 x 25 x 2	S2	2.066	9.60
45 x 25 x 3	S2	2.863	19.80
45 x 30 x 2	S2	2.223	10.90
45 x 30 x 2.5	S2	2.737	16.90
45 x 35 x 2	S2	2.380	10.50
50 x 10 x 2	S2	1.752	7.70
50 x 15 x 2	S2	1.909	7.80
50 x 20 x 1.5	S2	1.574	6.20
50 x 20 x 2	S2	2.066	6.90
50 x 20 x 2.5	S2	2.541	12.90
50 x 20 x 3	S1	2.863	11.30
50 x 20 x 3	S2	2.863	19.50
50 x 25 x 1.5	S2	1.692	6.80
50 x 25 x 2	S2	2.223	8.40
50 x 25 x 2.5	S2	2.737	12.90
50 x 25 x 3	S1	3.098	10.80
50 x 30 x 1.5	S2	1.810	7.10
50 x 30 x 2	S2	2.380	7.60
50 x 30 x 2.5	S1	2.933	9.70
50 x 30 x 2.5	S2	2.933	11.10
50 x 30 x 3	S1	3.334	9.80
50 x 30 x 3	S2	3.334	15.50
50 x 30 x 4	S1	4.252	17.80
50 x 34 x 2	S2	2.505	19.60
50 x 35 x 2	S2	2.537	12.10
50 x 35 x 3	S2	3.569	19.40
50 x 40 x 2	S2	2.694	9.90
50 x 40 x 2.5	S1	3.326	14.60
50 x 40 x 2.5	S2	3.326	16.20
50 x 40 x 3	S1	3.805	12.80
50 x 40 x 3	S2	3.805	18.90
55 x 25 x 2	S2	2.380	9.90
55 x 34 x 2	S2	2.662	14.70
60 x 20 x 1.5	S2	1.810	19.50
60 x 20 x 2	S2	2.380	9.50
60 x 20 x 3	S1	3.334	13.90

Rechteckstahlrohre

EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
 EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m



Abmessung mm		Gewicht kg/m	Basis Fr./m
60 x 20 x 3	S2	3.334	22.20
60 x 25 x 2	S2	2.537	10.30
2.5	S2	3.129	16.50
3	S2	3.569	49.00
60 x 30 x 2	S2	2.694	9.20
2.5	S2	3.326	13.00
3	S1	3.805	13.10
3	S2	3.805	16.50
4	S1	4.880	14.90
4	S2	4.880	29.00
60 x 33 x 3	S1	3.946	12.00
60 x 35 x 2	S2	2.851	14.00
3	S2	4.040	24.50
60 x 40 x 2	S2	3.008	9.90
2	S2, geschabt	3.008	12.40
2.5	S1	3.718	12.50
2.5	S2	3.718	14.20
3	S1	4.276	12.70
3	S2	4.276	16.90
4	S1	5.508	17.50
60 x 45 x 2	S2	3.165	19.90
3	S2	4.511	31.00
60 x 50 x 2	S2	3.322	15.60
3	S1	4.747	15.90
70 x 15 x 2	S2	2.537	14.40
70 x 20 x 2	S2	2.694	10.40
70 x 30 x 2	S2	3.008	10.90
3	S1	4.276	13.10
70 x 35 x 3	S1	4.511	17.00
70 x 40 x 2	S2	3.322	14.60
2.5	S2	4.111	22.00
3	S1	4.747	17.50
3	S2	4.747	31.00
4	S1	6.136	20.30
70 x 50 x 1.5	S2	2.752	22.00
2	S2	3.636	14.70
2.5	S2	4.503	22.50
3	S1	5.218	16.90
3	S2	5.218	28.00
4	S1	6.764	25.80
80 x 20 x 2	S2	3.008	9.90
2.5	S2	3.718	23.00
80 x 25 x 2	S2	3.165	19.00
3	S2	4.511	24.00
80 x 30 x 2	S2	3.322	12.90

Abmessung mm		Gewicht kg/m	Basis Fr./m
80 x 30 x 2.5	S2	4.111	20.50
3	S1	4.747	15.50
3	S2	4.747	25.00
80 x 34 x 2	S2	3.447	22.00
80 x 35 x 2	S2	3.479	21.00
2.5	S2	4.307	33.00
3	S2	4.982	41.00
80 x 40 x 2	S2	3.636	13.20
2.5	S2	4.503	21.00
3	S1	5.218	14.80
3	S2	5.218	24.00
4	S1	6.764	21.80
4	S2	6.764	40.50
80 x 45 x 3	S2	5.453	39.00
80 x 50 x 2	S2	3.950	15.40
2.5	S1	4.896	21.10
2.5	S2	4.896	26.00
3	S1	5.689	16.30
3	S2	5.689	29.50
4	S1	7.392	24.60
4	S2	7.392	49.00
5	S1	8.915	29.50
80 x 60 x 2	S2	4.264	22.80
3	S1	6.160	19.60
3	S2	6.160	37.00
4	S1	8.020	24.90
4	S2	8.020	46.00
90 x 20 x 2	S2	3.322	19.50
90 x 30 x 2	S2	3.636	19.70
90 x 50 x 3	S1	6.160	21.00
4	S1	8.020	26.70
100 x 20 x 2	S2	3.636	13.80
100 x 34 x 2	S2	4.075	23.00
100 x 40 x 2	S2	4.264	18.20
3	S1	6.160	19.40
3	S2	6.160	39.00
4	S1	8.020	26.00
100 x 50 x 2	S2	4.578	15.70
3	S1	6.631	18.90
3	S2	6.631	26.50
4	S1	8.648	23.80
100 x 60 x 3	S1	7.102	22.60
4	S1	9.276	26.20
100 x 80 x 3	S1	8.044	25.00
4	S1	10.532	33.00

Rechteckstahlrohre

EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m



Abmessung mm				Gewicht kg/m	Basis Fr./m	
120	x	40	x 2	S2	4.890	18.50
			3	S1	7.102	22.80
			4	S1	9.276	31.00
120	x	60	x 3	S1	8.044	23.10
			4	S1	10.532	32.30
120	x	80	x 4	S1	11.788	36.50
140	x	40	x 2.5	S2	6.858	41.00
140	x	50	x 3	S1	8.515	34.00
140	x	70	x 4	S1	12.416	51.00
150	x	50	x 3	S1	8.986	29.00

weitere Abmessungen auf Anfrage

- S1 (M) = rohschwarz, S235
- S2 (BKM) = gebeizt aus E195, E235 oder DD12
- S3 (WBKV) = aus Kaltband, mit schöner Oberfläche, gut biegsam
- S4 (SVZ) = sendzimirverzinkt
- geschabt = ohne Innengrat, ausgeschabte oder flachgerollte Innennaht