


Nahtlose Präzisionsstahlrohre geeignet für Druckleitungen (Hydraulikrohre)



EN 10305-4, normalgeglüht (+N), E235, gebondert, wirbelstromgeprüft, in HL von 6 m


Abmessungen mm	
4	x 0.5* 1*
5	x 1*
6	x 1* 1.5* 2*
7	x 1.5*
8	x 1* 1 1.5* 2*
10	x 1* 1 1.5 2 2.5
12	x 1* 1 1.5 2 2.5
14	x 1 1.5 2 2.5 3.5
15	x 1* 1 1.5 2 2.5
16	x 1 1.5* 1.5 2 2.5 3
17	x 3
18	x 1 1.5 2 2.5 3
20	x 1.5

Abmessungen mm	
20	x 2 2.5 3 3.5 4
22	x 1.5* 1.5 2 2.5 3
25	x 1.5 2 2.5 3 3.5 4 4.5 5
26	x 3
27	x 3.5
28	x 1.5 2* 2 2.5 3 4
30	x 2 2.5 3 4 5 6
32	x 2.5
33	x 4
35	x 2 2.5 3
38	x 2.5 3 4 5 7
40	x 2 3

Abmessungen mm	
42	x 2 3 4 5
48	x 5
50	x 3 4 6 9
60	x 5 6
65	x 8
80	x 10

Abmessungen mm	
* = ungebondert	

Nahtlose Präzisionsstahlrohre geeignet für Druckleitungen (Hydraulikrohre)



EN 10305-4, normalgeglüht (+N), E235, galvanisch verzinkt und passiviert, wirbelstromgeprüft, in HL von 6 m

Abmessungen mm		
4	x	1
6	x	1 1.5
8	x	1 1.5
10	x	1 1.5 2
12	x	1 1.5 2
14	x	2
15	x	1 1.5 2
16	x	1.5 2 3
18	x	1.5 2
20	x	1.5 2 2.5 3
22	x	1.5 2 2.5
25	x	2.5 3 4.5
28	x	1.5 2 2.5 3
30	x	3 4
35	x	2 3
38	x	4 5
42	x	2 3

