


Geschweisste Präzisionsstahlrohre

EN 10305-3, geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m

EN 10305-2, geschweisst, kaltgezogen ohne Innengrat, E235, in HL von 4 - 7 m




Abmessung Mm		Gewicht kg/m	Basis Fr./m
6 x 1	S2	0.123	3.60
8 x 1	S3	0.173	2.60
8 x 1.5	S2	0.240	4.90
9 x 1	S2	0.197	7.40
9 x 1.5	S2	0.277	8.80
10 x 1	S3	0.222	1.70
10 x 1.5	S2	0.314	2.20
10 x 1.5	S3	0.314	2.80
10 x 2	S2	0.395	6.30
11 x 1	S2	0.247	5.00
12 x 1	S3	0.271	1.90
12 x 1.5	S2	0.388	2.10
12 x 1.5	S3	0.388	2.60
12 x 2	S2	0.493	2.70
13 x 1	S3	0.296	2.20
13 x 1.5	S2	0.425	2.60
13 x 2	S2	0.543	3.40
14 x 1	S3	0.321	2.20
14 x 1.5	S2	0.462	2.40
14 x 2	S2	0.592	2.60
14 x 2	S3	0.592	3.40
15 x 1	S3	0.345	1.90
15 x 1.2	S2	0.408	2.40
15 x 1.5	S2	0.499	2.60
15 x 2	S2	0.641	3.20
15 x 2	S3	0.641	4.10
16 x 1	S3	0.370	2.90
16 x 1.2	S2	0.438	3.00
16 x 1.5	S2	0.536	2.70
16 x 2	S2	0.691	3.00
16 x 2	S3	0.691	3.90
17 x 1	S3	0.395	4.30
17 x 1.5	S2	0.573	8.00
17 x 2	S2	0.740	3.70
17.2 x 2	S2	0.750	3.50
18 x 1	S3	0.419	3.80
18 x 1.2	S2	0.497	3.10
18 x 1.5	S2	0.610	2.80
18 x 1.5	S3	0.610	3.60
18 x 2	S2	0.789	3.10
18 x 2	S3	0.789	4.10
19 x 1	S2	0.444	5.70
19 x 1.5	S2	0.647	7.00
19 x 2	S2	0.838	9.20
20 x 1	S3	0.469	3.00
20 x 1.2	S2	0.556	3.40

Abmessung mm		Gewicht kg/m	Basis Fr./m
20 x 1.5	S2	0.684	2.70
20 x 1.5	S3	0.684	3.70
20 x 2	S2	0.888	3.30
20 x 2	S3	0.888	4.50
20 x 2.5	S2	1.079	4.70
21.3 x 2	S2	0.952	3.70
22 x 1	S2	0.518	6.00
22 x 1.2	S2	0.616	3.70
22 x 1.5	S2	0.758	2.90
22 x 1.5	S3	0.758	3.90
22 x 1.5	gezogen	0.758	7.90
22 x 2	S2	0.986	3.70
22 x 2	S3	0.986	5.00
22 x 2.5	S2	1.202	7.80
22 x 3	S2	1.406	21.00
23 x 1.5	S2	0.795	12.50
24 x 1	S3	0.567	5.20
24 x 1.5	S2	0.832	11.00
24 x 2	S2	1.085	4.80
24 x 2.5	gezogen	1.326	13.50
25 x 1	S3	0.592	3.50
25 x 1.2	S2	0.704	8.30
25 x 1.5	S2	0.869	3.70
25 x 2	S2	1.134	4.10
25 x 2	S3	1.134	5.60
25 x 2.5	S2	1.387	5.70
25 x 3	S2	1.628	6.50
26 x 1	S3	0.617	6.80
26 x 1.5	S2	0.906	5.00
26 x 2	S2	1.184	6.90
26 x 2	S3	1.184	9.30
26 x 3	S2	1.702	9.40
26.9 x 2	S2	1.228	4.70
28 x 1	S2	0.666	3.30
28 x 1.5	S2	0.980	4.10
28 x 1.5	S3	0.980	5.60
28 x 2	S2	1.282	4.70
28 x 2	S3	1.282	6.40
28 x 2	gezogen	1.282	16.50
28 x 2.5	S2	1.572	6.20
28 x 2.5	gezogen	1.572	19.40
30 x 1	S2	0.715	5.00
30 x 1.5	S2	1.054	4.00
30 x 1.5	gezogen	1.054	14.40
30 x 2	S2	1.381	5.00
30 x 2	S3	1.381	7.00

Geschweisste Präzisionsstahlrohre

EN 10305-3, geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m

EN 10305-2, geschweisst, kaltgezogen ohne Innengrat, E235, in HL von 4 - 7 m



Abmessung Mm		Gewicht kg/m	Basis Fr./m
30 x 2.5	S2	1.695	7.10
	S2	1.998	8.60
32 x 1.2 (6420 mm)	S3	0.911	8.90
	S2	1.128	4.80
	S2	1.480	9.00
	S3	1.480	12.60
	S2	2.146	13.70
33.7 x 2	S2	1.564	5.30
34 x 2	S2	1.578	7.20
35 x 1	S2	0.838	5.00
	S2	1.239	5.90
	S2	1.628	6.40
	S3	1.628	8.90
	S2	2.004	8.40
	S3	2.004	11.80
36 x 2	S2	1.677	13.00
37 x 1.5	S2	1.313	8.40
38 x 1	S2	0.888	5.00
	S2	1.350	5.50
	S2	1.776	6.50
40 x 1	S2	0.962	6.50
	S2	1.424	5.90
	S2	1.874	6.80
	S3	1.874	9.80
	S2	2.312	8.50
	S3	2.312	11.90
41 x 1.5	S3	1.461	10.60
	S3	1.011	11.30
42 x 1.5	S2	1.498	6.90
	S3	1.498	9.70
42 x 2	S2	1.973	8.00
	S2	1.993	6.80
43 x 1.5	S2	1.535	8.50
	S4 (Alu)	1.535	8.50
45 x 1.5	S2	1.609	7.50
	S3	1.609	10.80
	S2	2.121	9.20
	S2	2.620	11.50
	S2	3.107	12.90
48.3 x 2	S2	2.284	8.70
50 x 1	S3	1.208	9.30
	S2	1.794	7.30
	S2	2.368	7.90
	S3	2.368	11.30
	S2	2.929	11.10

Abmessung mm		Gewicht kg/m	Basis Fr./m
50 x 3	S2	3.477	14.20
	S2	4.538	47.00
52 x 1.5	S2	1.868	27.00
55 x 1.5	S2	1.979	10.70
	S2	2.614	14.00
60 x 1	S2	1.455	8.70
	S2	2.164	9.10
	S2	2.861	10.30
	S3	2.861	14.50
60.3 x 2	S2	4.217	18.70
	S2	2.876	11.20
60.3 x 4	S1	5.554	19.00
	S2	3.107	17.00
70 x 1	S2	1.702	57.00
	S2	2.534	11.20
	S3	2.534	15.80
	S2	3.354	13.50
70 x 2	S1	6.511	26.00
	S2	2.719	22.50
76.1 x 6.3	S1	10.845	49.00
80 x 1.5	S2	2.904	30.00
	S2	3.847	16.20
	S3	3.847	22.70
83 x 2	S2	3.995	34.00
88.9 x 8	S1	15.961	58.00
89 x 2	S2	4.291	23.20
102 x 2	S2	4.932	29.80
108 x 2	S2	5.228	34.00

weitere Abmessungen auf Anfrage

- S1 (M) = rohschwarz aus E235
- S2 (BKM) = gebeizt aus E195, E235 oder DD12
- S3 (WBKV) = aus Kaltband, mit schöner Oberfläche, gut biegsam
- S4 (Alu) = aus aluminisiertem Band geschabt = ohne Innengrat, ausgeschabte oder flachgerollte Innennaht
- gezogen = kaltgezogen ohne Innengrat