


# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	
20	x 4
	5
21.3	x 4
	5
25	x 2.3
	5
	6.3
26.9	x 4
	5
30	x 4
	5
	6.3
	8
31.8	x 4
	5
	8
32	x 6
	8
33.7	x 4
	5
	6.3
	8
36	x 5.5
	8
38	x 5
	8
	10
40	x 6
	7.5
	10
42.4	x 4
	5
	6.3
	7.1
	8
	10
	12.5
44.5	x 5
	7.1
	8
	10
45	x 6.5
	8.5
	12.5
48.3	x 2.9
	4.5


Abmessungen mm	
48.3	x 5
	6.3
	7.1
	8
	10
	12.5
50	x 7
	9
	12.5
51	x 4
	5
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
54	x 5
	7.1
	10
55	x 13.5
56	x 8
	10
	14
57	x 4
	5
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
60	x 17.5
60.3	x 3.6
	4
	4.5
	5
	5.6
	6.3
	7.1
	8
	10
	11

Abmessungen mm	
60.3	x 12.5
	14.2
	16
63	x 6.5
	9
	11.5
	13.5
	15.5
63.5	x 5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
65	x 18.5
70	x 5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.5
71	x 7.5
	10.5
	13
	15.5
	17.5
73	x 10
	14.2
	16
	17.5
75	x 7.5
	9.5
	12.5
	15
	20

Abmessungen mm	
75	x 22.5
76.1	x 4.5
	5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
80	x 8.5
	12
	15
	17.5
	20
82.5	x 4.5
	5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
85	x 9
	12
	15
	17.5
	20
	25
	27.5
88.9	x 4
	4.5
	5
	5.6
	6.3

# Nahtlose Starkwandrohre


Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	Abmessungen mm	Abmessungen mm	Abmessungen mm
88.9 x 7.1	101.6 x 12.5	114.3 x 20	127 x 30
8	14.2	22.2	36
8.8	16	25	40
10	17.5	28	130 x 45
11	20	36	50
12.5	22.2	115 x 40	132 x 13
14.2	25	118 x 11.5	21
16	28	14	26
17.5	30	19	30.5
20	106 x 10.5	23.5	133 x 5
22.2	13	27.5	5.6
25	17.5	30	6.3
90 x 9.5	21.5	121 x 7.1	7.1
11.5	25	8	8
13.5	108 x 5	10	10
17	6.3	11	11
20	7.1	12.5	12.5
27.5	8	14.2	14.2
30	8.8	16	16
95 x 8	10	20	17.5
10	11	25	20
12.5	12.5	30	22.2
14	14.2	36	25
16	16	40	28
17.5	17.5	125 x 12.5	30
19.5	20	15	32
20	22.2	17.5	36
22.5	25	22.5	40
25	28	27	139.7 x 5
30	32	42.5	5.6
100 x 7.5	112 x 11	127 x 5	6.3
10	13.5	5.6	7.1
12.5	16	6.3	8
14.5	20.5	7.1	10
18.5	24.5	8	12.5
22	114.3 x 5	8.8	14.2
32.5	5.6	10	16
35	6.3	11	17.5
101.6 x 4.5	7.1	12.5	20
5	8	14.2	22.2
5.6	10	16	25
6.3	11	17.5	28
7.1	12.5	20	30
8	14.2	22.2	35
8.8	16	25	40
10	17.5	28	140 x 14

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	
140	x 17
	20
	25
	30
	37.5
	45
	47.5
	50
146	x 7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	25
	30
150	x 12.5
	22
	35
	47.5
152.4	x 5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	36
	40
	45
	50
159	x 5.6
	6.3
	7.1


Abmessungen mm	
159	x 8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	40
	45
	50
160	x 24
	35
	60
165.1	x 7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	36
	40
	60
168.3	x 5.6
	6.3
	7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25

Abmessungen mm	
168.3	x 28
	30
	40
170	x 15
	26
	35
171	x 10
	12.5
	14.2
	16
	17.5
	20
	25
	30
	36
	40
	45
	50
177.8	x 5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	35
	40
	45
180	x 15
	20
	27.5
	40
	60
190	x 15
	20
	22
	29
	42

Abmessungen mm	
190	x 50
	60
193.7	x 6.3
	7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	36
	40
	45
	50
200	x 20
	30
	44
	65
	70
203	x 6.3
	7.1
	8
	8.8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	40
	45
	50
212	x 21

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	
212	x 31
	43.5
	60
219.1	x 7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	40
	45
	50
224	x 22
	32
	46
	50
	55
	60
229	x 10
	12.5
	14.2
	17.5
	20
	25
	30
	35
	36
	40
	45
	50
236	x 23
	33
	48
	55
	60
244.5	x 7.1
	8

Abmessungen mm	
244.5	x 10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	36
	40
	45
	50
	60
	70
250	x 25
	35
	50
	65
254	x 7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	25
	28
	30
	35
	40
	45
	52
	60
	70
267	x 7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20

Abmessungen mm	
267	x 22.2
	25
	28
	30
	35
	36
	40
	45
	50
	55
	60
	70
	80
273	x 10
	12.5
	16
	20
	25
	30
	35
	40
	45
	50
	60
	70
	80
279	x 12.5
	14.2
	17.5
	20
	25
	30
	36
	40
	50
	60
	70
	80
292	x 12.5
	16
	17.5
	25
	30
	36
	40
	45

Abmessungen mm	
292	x 50
	60
298.5	x 8
	10
	12.5
	14.2
	16
	20
	25
	28
	30
	35
	40
	50
	60
	70
	80
305	x 10
	12.5
	14.2
	17.5
	20
	25
	30
	36
	40
	45
	50
	55
	60
	65
	70
	80
	92.5
318	x 10
	16
	20
	25
	30
	36
	40
	45
	50
323.9	x 8
	10
	12.5

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm
323.9 x 14.2
16
17.5
20
22.2
25
28
30
36
40
45
50
55
60
65
70
80
90
330 x 20
343 x 12.5
16
20
22.2
25
30
35
40
45
50
60
65
70
75
355.6 x 10
12.5
14.2
17.5
20
22.2
25
30
36
40
50
55
60

Abmessungen mm
355.6 x 70
80
100
368 x 10
12.5
14.2
16
20
22.2
25
28
30
35
40
45
50
60
70
80
90
100
394 x 14.2
16
20
30
35
36
40
50
55
60
70
406.4 x 10
12.5
14.2
16
20
22.2
25
30
35
40
45
50
55
60

Abmessungen mm
406.4 x 70
80
90
100
412 x 11
419 x 12.5
14.2
17.5
20
25
30
40
45
50
60
70
90
100
445 x 16
17.5
20
25
36
40
50
60
70
457 x 12.5
17.5
20
25
30
40
50
60
70
80
100
470 x 17.5
20
30
40
50
60
80
495 x 12.5

Abmessungen mm
495 x 30
40
50
100
508 x 16
20
25
30
40
50
60
70
80
100
521 x 20
40
50
559 x 14.2
20
25
30
40
50
60
80
610 x 20
25
50
60
622 x 40
50
60
100