

Vierkantstahlrohre

EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
 EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m



Abmessung mm		Gewicht kg/m	Basis Fr./m
9 x 9 x 1	gezogen	0.249	4.60
10 x 10 x 1	S2	0.281	1.70
	1.5 S2	0.397	2.10
12 x 12 x 1	S2	0.344	2.30
	1.5 S2	0.491	2.60
14 x 14 x 1.5	S2	0.585	3.30
15 x 15 x 1	S2	0.438	2.70
	1.5 S2	0.632	2.90
	2 S2	0.810	3.30
16 x 16 x 1.5	S2	0.679	3.60
	2 S2	0.872	4.60
18 x 18 x 1	S2	0.532	3.20
	1.5 S2	0.773	4.00
	2 S2	0.998	5.60
20 x 20 x 1	S2	0.595	2.70
	1.5 S2	0.868	3.40
	2 S2	1.124	3.90
	2.5 S1	1.363	7.20
	2.5 S2	1.363	8.10
	3 S1	1.450	8.30
22 x 22 x 1.5	S2	0.962	5.30
	2 S2	1.249	6.90
25 x 25 x 1	2.5 S2	1.520	9.30
	S2	0.752	4.10
	1.5 S2	1.103	4.40
	2 S2	1.438	5.00
	2.5 S1	1.756	6.50
	2.5 S2	1.756	7.10
28 x 28 x 2	3 S1	1.921	9.10
	3 S2	1.921	10.10
30 x 30 x 2	S2	1.626	8.90
	2.5 S2	1.991	13.20
30 x 30 x 1.5	S2	1.339	5.20
	1.5 S4 (SVZ)	1.339	6.80
	2 S2	1.752	6.10
	2 S3	1.752	9.30
	2 S2, geschabt	1.752	8.00
	2.5 S1	2.148	7.20
32 x 32 x 2	2.5 S2	2.148	8.20
	2.5 S3	2.148	12.50
	3 S1	2.392	7.30
	3 S2	2.392	9.60
34 x 34 x 2	S2	1.877	11.30
	2.5 S2	2.305	14.30

Abmessung mm		Gewicht kg/m	Basis Fr./m
35 x 35 x 1.5	S2	1.574	6.30
	2 S2	2.066	7.10
	2 S2, geschabt	2.066	9.30
	2.5 S1	2.541	9.20
	2.5 S2	2.541	10.00
	3 S1	2.863	9.70
38 x 38 x 2	3 S2	2.863	13.50
38 x 38 x 2	S2	2.254	13.70
	3 S2	3.145	20.20
40 x 40 x 1.5	S2	1.810	7.20
	2 S2	2.380	7.80
	2 S2, geschabt	2.380	10.20
	2.5 S1	2.933	9.90
	2.5 S2	2.933	10.60
	3 S1	3.334	10.10
45 x 45 x 2	3 S2	3.334	13.20
	4 S1	4.252	12.90
	4 S2	4.252	23.00
45 x 45 x 2	S2	2.694	9.90
	2.5 S1	3.326	11.90
	2.5 S2	3.326	13.20
	3 S1	3.805	16.10
50 x 50 x 1.5	3 S2	3.805	20.60
50 x 50 x 1.5	S2	2.281	15.00
	1.5 S4	2.281	19.50
	2 S2	3.008	10.00
	2 S2, geschabt	3.008	13.00
	2.5 S1	3.718	12.30
	2.5 S2	3.718	14.10
55 x 55 x 1.5	3 S1	4.276	12.90
	3 S2	4.276	15.90
	4 S1	5.508	16.10
	4 S2	5.508	30.80
	5 S1	6.560	19.80
55 x 55 x 1.5	S2	2.516	14.80
	2 S2	3.322	15.80
	3 S2	4.747	29.90
	5 S1	7.345	39.00
60 x 60 x 2	S2	3.636	13.60
	2 S2, geschabt	3.636	17.70
	2.5 S1	4.503	14.90
	2.5 S2	4.503	16.50
	3 S1	5.218	15.20
	3 S2	5.218	20.20
60 x 60 x 2	4 S1	6.764	20.40
	4 S2	6.764	34.10

Vierkantstahlrohre



EN 10305-5, S2 (BKM), geschweisst, kaltgewalzt, E195, E235, DD12, in HL von 6 m
 EN 10219, S1 (M), geschweisst, kaltgewalzt, S235, in HL von 6/12 m

Abmessung mm				Gewicht kg/m	Basis Fr./m	
60	x	60	x 5	S1	8.130	23.90
70	x	70	x 2	S2	4.264	16.40
				S1	6.160	19.90
				S2	6.160	39.90
				S1	8.020	24.00
				S2	8.020	55.00
80	x	80	x 2	S2	4.892	18.90
				S1	7.102	22.40
				S2	7.102	34.90
				S1	9.276	26.10
				S2	9.276	56.00
				S1	11.270	31.90
90	x	90	x 3	S1	8.044	26.00
				S1	10.532	34.00
100	x	100	x 3	S1	8.986	26.80
				S1	11.788	33.50
				S2	11.788	86.00
				S1	14.410	43.90
120	x	120	x 3	S1	10.870	35.10
				S1	14.300	43.80
				S1 ^{S355}	26.408	79.70
140	x	140	x 3	S1	12.754	38.90

Abmessung mm	Gewicht kg/m	Basis Fr./m
-----------------	-----------------	----------------

weitere Abmessungen auf Anfrage

- S1 (M) = rohschwarz aus E235
- S2 (BKM) = gebeizt aus E195, E235 oder DD12
- S3 (WBKV) = aus Kaltband, mit schöner Oberfläche, gut biegsam
- S4 (SVZ) = sendzimirverzinkt
- geschabt = ohne Innengrat, ausgeschabte oder flacherollte Innennaht